

Lunada Bay Tile is pleased to expand its partnership with Tommy Bahama® in creating Kapa, a captivating collection of handcrafted concrete tiles.

Reinterpreting Tommy Bahama's most iconic textile prints, Kapa architectural concrete tiles are inspired by elements of the exotic: sumptuous tropical fabrics, lush palm fronds, and waves lapping along a quiet shoreline. The embossed relief surfaces spark vacation daydreams and sanguine memories. Handcrafted in California, the dimensional surfaces add subtle, luxe texture to walls and coordinate with Tommy Bahama and Lunada Bay Tile glass collections.



Please visit [LunadaBayTile.com](https://LunadaBayTile.com) for our complete product offerings, applications and installation instructions.



© 2024 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE			FLOOR APPLICATIONS		
Application	Suitable			Interior	Exterior
Interior Wall/Backsplash	Yes		Shower	No	No
Fireplace/Cooktop Surround	Yes *		Steam Shower	No	N/A
Shower Wall	Yes		Light Residential	No	No
Steam Shower	No		Residential	No	No
Exterior Wall	Yes				
Pool, Spa or Water Feature (fully submerged)	No				
PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage	Packaging (Per Box)			
Homespun (6 x 12")	2.109 Pieces / SF	6 Pieces / 2.845 SF	Breaking Strength	ASTM C-648	> 16,000 PSI
Homespun Liner (1 1/2 x 12")	1.021 Pieces / LF	18 Pieces / 17.622 LF	Water Absorption	ASTM C-373	Vitreous ≥ .05% - ≤ 3.0%
Lewa (6 x 12")	2.109 Pieces / SF	6 Pieces / 2.845 SF	Chemical Resistance	ASTM C-650	Passed
Palm Retreat (6 x 12")	2.109 Pieces / SF	6 Pieces / 2.845 SF	Freeze/Thaw	ASTM C-1026	Unaffected
Shangri-La (6 x 12")	2.109 Pieces / SF	6 Pieces / 2.845 SF	Warpage	ASTM C-485	± 0.26% / ± 1.5mm
Tide Dye (6 x 12")	2.109 Pieces / SF	6 Pieces / 2.845 SF			
Shade Variation	Grout Joint Recommendation		NOTES		
V3 - V4 Substantial Variation	1/8" (3 mm)		<p>Since variations are common in artistic concrete tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. On dimensional patterns, using a grout bag is the best method to target competent and successful grout application. Grout floats should not be used. Please take care when grouting and protect surface from abrasion. <b>Installation constitutes acceptance.</b> We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).</p>		
			MAINTENANCE		
			<p>A routine cleaning of <b>Tommy Bahama Kapa</b> can be done with light duty, diluted close to neutral pH cleaner.</p>		

\* Acceptable for limited and sporadic exposure near open flame or heat source, such as a fireplace. It is not recommended for placement on a backsplash behind a cooktop, or inside a firebox.

**FLOOR APPLICATION DEFINITIONS:**  
**Light Residential** - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.  
**Residential** - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.