

	SPECIALTY DOORS	DESIGNER FIBERGLASS	SPECIALTY VINYL	CONTEMPORARY ALUMINUM		
		8680	8700	8800*	8850*	8450
INSULATION	Insulation type	Polyurethane	Polyurethane	Polyurethane (optional)	Polyurethane (optional)	
	U-factor†	0.15	0.24	0.27 low E glass 0.29 Ins glass	0.28 low E glass 0.31 Ins glass	N/A
DOOR SIZE AND CONSTRUCTION	R-value*	12	11.75	<4.36	<4.06	N/A
	Counterbalance	Torsion	Torsion	Torsion	Torsion	Torsion
	Height (minimum/maximum)	6'6"/14'	6'14"	6'9"1"	6'12"	6'17"/19"
	Width (minimum/maximum)	6'18"	8'18"	6'18"2"	6'18"	6'18"
	Width increments	Common	Common	1"	1"	1"
	Section heights (inches)	16, 22, 24, 26, 28	18, 21	Equal	Equal	Equal
	Construction layers	Fiberglass/Steel/Insulation/Steel	Vinyl/Insulation/Vinyl	Aluminum frame	Aluminum frame	Aluminum frame
DESIGN/WINDOW OPTIONS	Section thickness	1"	1-1/2"	2"	1-5/16"	1-5/8"
	Section joint	Tongue-and-groove	Tongue-and-groove	Tongue-and-groove	Tongue-and-groove	Tongue-and-groove
	Joint-to-joint seal		•	•	•	•
	Design options	4 designs	2 designs	N/A	N/A	N/A
	Decorative windows		•			
	Divided windows	•				
	Vertical Column windows	•				
	Clear	•	•	•	•	•
	Gray Tinted	•		•	•	•
	Green Tinted	•		•	•	•
GLASS OPTIONS	Bronze Tinted	•		•	•	•
	Satin Etched	•		•	•	•
	White Laminated	•		•	•	•
	Obscure	•		•	•	•
	Polycarbonate					
	Opaque White					•
	Opaque Black					•
	Mirrored Gray					•
	Mirror Bronze					•
	Translucent Black					•
MISC.	Decorative hardware	•				
	Wind Load available					
	Warranty	Limited Lifetime	15-Year	One-Year	One-Year	One-Year
	Price	\$\$\$\$\$	\$\$\$	\$\$\$\$\$	\$\$\$\$\$	\$\$\$\$\$\$\$

	COLOR OPTIONS	DESIGNER FIBERGLASS	SPECIALTY VINYL	CONTEMPORARY ALUMINUM		
		8680	8700	8800	8850	8450
PAINT FINISHES	Glacier White		•			
	Adobe Cream		•			
	Monterey Sand		•			
	Cape Cod Gray		•			
	White					•
STAIN FINISHES	Brown				•	
	White		•			
	Clay		•			
	Gray		•			
	Green		•			
	Honduran Mahogany		•			
	Mahogany		•			
	Natural Oak		•			
	Red Oak		•			
	Cherry		•			
ALUMINUM FINISHES	Walnut		•			
	Clear Anodized				•	•
	Dark Bronze Anodized				•	•
	Black Anodized				•	•
	White Powder Coat				•	•
	Dark Bronze Powder Coat				•	•
	Black Powder Coat				•	•
RAL Powder Coat				•	•	




Model 8300, Sonoma Ranch panel, Brown finish, Arched Stockton IV windows, Decorative hardware

Garage Door Design Center

To see this door on your home, visit wayne-dalton.com, or download our Garage Door Design Center app. Upload a photo of your home and experiment with panel designs, color options, window styles and decorative hardware designs. Instant curb appeal awaits you with just a click of your mouse.

THERMAL PERFORMANCE



Wayne Dalton participates in the DASMA Thermal Performance Verification Program. The program verifies the thermal performance of sectional garage doors. The lower the U-factor rating, the better the thermal performance.



Symbol indicates verified U-factor rating in accordance with the DASMA Thermal Performance Verification Program.



DISTRIBUTED BY:

2501 S. State Hwy. 121 Bus., Ste 200
Lewisville, TX 75067

wayne-dalton.com



© 2024 Wayne Dalton, a Division of Overhead Door Corporation. Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation. Item W900-1059 02/24

Wayne Dalton GARAGE DOORS Comparison Guide

RESIDENTIAL GARAGE DOORS



Model 8300AG, Contemporary panel, Beachwood plank Wood Grain Impressions™ finish, Clear IV windows



Model 8680, 8' Horizontal V-Groove panel, Natural Oak finish, Vertical windows



Model 8800 Black anodized, White Laminated glass

	WOOD DOORS	7000 SERIES	
		7100	7400
INSULATION	Insulation type	Polystyrene (optional)	Polystyrene (optional)
	R-value*	<2	4.75
DOOR SIZE AND CONSTRUCTION	Torsion counterbalance	•	•
	Width (minimum/maximum)**	6'18"	6'18"
	Available width increments	8', 9', 10', 12', 16', 18'	8', 9', 10', 12', 16', 18'
	Construction	Rail and stile	Flush with overlay
	Section thickness*	1-5/8"	2"
	Section joint	Shiplap	Shiplap
	Stain grade	•	•
WOOD TYPE	Paint grade	•	•
	T1-11 4" Grooves Plywood	Optional on some models	Optional on some models
	T1-11 8" Grooves Plywood	Optional on some models	Optional on some models
	Medium Density Overlay (MDO)	Optional on some models	Optional on some models
	Smooth/Luan Plywood	Optional on some models	Optional on some models
	Rough Sawn Plywood	Optional on some models	Optional on some models
	Hemlock	Optional on some models	Optional on some models
	Western Red Cedar	Optional on some models	Optional on some models
	Knotty Cedar	Optional on some models	Optional on some models
	Mahogany	Optional on some models	Optional on some models
GLASS OPTIONS	Clear	•	•
	Satin Etched	•	•
	Obscure	•	•
MISC.	Carriage House design options	5 designs	6 designs
	Divided windows	•	•
	Decorative hardware	•	•
MISC.	Wind load available***	•	•
	Warranty	1-Year Limited	1-Year Limited

*Wayne Dalton uses a calculated door section R-value for our insulated doors.
**Some heights and widths will be special order. Contact Customer Service for details.
***See wind load document on each product for details and ratings.
*Section thickness may vary slightly depending on wood type.



Model 7409, Harrington Arched panel, Natural Oak finish, 12 Lite Double windows

STEEL DOORS		INSULATION		COUNTERBALANCE		DOOR SIZE			DOOR CONSTRUCTION						PANEL DESIGN						WINDOW OPTIONS			GLASS OPTIONS						STEEL DOORS																											
MODEL	Insulation type	U-factor ¹ / R-value*	Torsion	TorqueMaster [®] Plus	Width (min/max)	Width increments	Height (min/max)	Section heights (inch)	Construction	Section thickness	Section joint	Joint-to-joint seal	Thermal break	Wind load***	Colonial	Ranch	Sonoma	Sonoma Ranch	Contemporary	Ridgefield	Riverton	Carriage House designs	Decorative windows	Vertical column	Impact glazing	Clear	Gray Tinted	Green Tinted	Bronze Tinted	Satin Etched Privacy	Obscure	Decorative hardware	Total Pack**	Warranty†	Price	MODEL																					
CARRIAGE HOUSE STEEL																													CARRIAGE HOUSE STEEL																												
8670	Polyurethane	0.16 / 11			6'18"	1"	6'6"/12'	20.8, 23.8, 25.73, 28	Steel/Insulation/Steel	1-5/8"	Tongue-and-groove	•	•									11 designs	•			•	•	•	•	•	•			Limited Lifetime	\$\$\$\$	8670																					
6600	Polyurethane	0.15 / 12.12			6'18"	Common ¹	7'9"	20.8, 24	Steel/Insulation/Steel	1-3/8" + Overlay	Tongue-and-groove	•	•	•								11 designs	•		•	•			•	•			Limited Lifetime	\$\$\$	6600																						
9405	Polyurethane	0.27 / 10	•	•	6'9"	Common ²	6'9"	20.8, 23.8	Steel/Insulation/Steel	1-1/4" + Integrated strut	Pinch-resistant	•		•								8 designs	•		•	•	•	•	•	•			Limited Lifetime	\$	9405																						
CLASSIC STEEL																													CLASSIC STEEL																												
8500	Polyurethane	0.12 / 16.22	•		6'20"	1"	6'14"	18, 20.8, 24	Steel/Insulation/Steel	2"	Tongue-and-groove	•	•	•	•	•	•	•	•	•				•	•	•	•	•	•	•			Limited Lifetime	\$	8500																						
8300	Polyurethane	0.15 / 12.12	•	•	4'20"	1"	4'14"	18, 20.8, 24	Steel/Insulation/Steel	1-3/8"	Tongue-and-groove	•	•	•	•	•	•	•	•	•				•	•	•	•	•	•	•			Limited Lifetime	\$	8300																						
9605	Polyurethane	0.26 / 10	•	•	4'18"	6"	7'13"11"	19.1, 20.8, 23.8	Steel/Insulation/Steel	1-1/4" + Integrated strut	Pinch-resistant	•		•	•	•	•	•	•					•	•	•	•	•	•	•			Limited Lifetime	\$	9605																						
9100	Polyurethane	0.25 / 9	•	•	6'18"	6"	6'9"	19.1, 20.8, 23.8	Steel/Insulation/ToughGard	1" + Integrated strut	Pinch-resistant	•		•	•	•	•	•	•					•	•	•	•	•	•	•			Limited Lifetime	\$	9100																						
8200	Polystyrene	7.4	•	•	5'20"4"	Common ³	6'14"	18, 21	Steel/Insulation/Vinyl	2"	Tongue-and-groove	•		•	•	•	•	•						•	•	•	•	•	•			10-Year	\$	8200																							
8000	--	--	•	•	5'20"	Common ³	6'14"	18, 21	Steel	2"	Tongue-and-groove	•		•	•	•	•	•						•	•	•	•	•	•			10-Year	\$	8000																							
8224	Polystyrene	7.4	•	•	5'18"	Common ³	6'14"	18, 21	Steel/Insulation/Vinyl	2"	Tongue-and-groove	•		•	•	•	•	•						•	•	•	•	•	•			10-Year	\$	8224																							
8024	--	--	•	•	5'18"	Common ³	6'14"	18, 21	Steel	2"	Tongue-and-groove	•		•	•	•	•	•						•	•	•	•	•	•			10-Year	\$	8024																							
DESIGNER STEEL																													DESIGNER STEEL																												
8310	Polyurethane	0.15 / 12.12	•	•	6'20"	1"	6'14"	20.8, 23.8, 28	Steel/Insulation/Steel	1-5/8"	Tongue-and-groove	•								•	•				•	•	•	•	•			10-Year	\$	8310																							

Width increments:
 1= 6', 7', 8', 9', 10', 12', 14', 15', 16', 18' 2= 6', 8', 9', 10', 15', 16', 18' 3= 6', 7', 8', 9', 10', 11', 12', 14', 15', 15'6", 15'8", 16', 17', 18', 20'

COLOR OPTIONS	PAINT FINISHES											TWO-TONE PAINT FINISHES						WOOD GRAIN FINISHES			WOOD GRAIN IMPRESSIONS™ FINISHES				STAIN FINISHES							COLOR OPTIONS																									
	White	Almond	Desert Tan	Taupe	Sandstone	Gray	Terra Bronze	Green	Brown	Black	Clay	Green/White	Gray/White	Clay/White	White/White	Almond/White	Taupe/White	Terra Bronze/White	Brown/White	Black/White	Golden Oak	Mission Oak	Walnut	Cedar	Beachwood	Medium Oak	Carbon Oak	Clay	Gray	Green	Honduran Mahogany		Mahogany	Natural Oak	Red Oak	Walnut	TruChoice™ Color System																				
CARRIAGE HOUSE STEEL																													CARRIAGE HOUSE STEEL																												
8670	•											•	•	•																						•	8670																				
8600																																				•	8600																				
9405	•	•										•	•	•																					•	9405																					
CLASSIC STEEL																													CLASSIC STEEL																												
8500	•	•																																	•	8500																					
8300	•	•																																	•	8300																					
9605	•	•																																	•	9605																					
9100	•	•																																			9100																				
8200	•	•																																		8200																					
8000	•	•																																		8000																					
8224	•	•																																		8224																					
8024	•	•																																		8024																					
DESIGNER STEEL																													DESIGNER STEEL																												
8310	•	•																																	•	8310																					

For selection of windows for each product refer to Window Guide. With any of the above configurations, some product options may have additional limitations. See product literature for additional details.
 *Wayne Dalton uses a calculated door section R-value for our insulated doors.
 **Total Pack doors include weather stripping for top and sides. Product size limitations depend on product series.
 ***See wind load documents on website for details. Actual colors may vary from brochure due to fluctuations in the printing process. Always request a color sample from your Dealer for accurate color matching before ordering your door.
 †U-factor is independently tested and verified per ANSI/DASMA 105 using solid doors and specific product sizes.