

# Gotham®

## Porcelain Stone®

### Sizes Available in all colors

2 x 6

12 x 24



AV325 ▶ Dockside 12 x 24

### Sizes & Finishes

#### Field Tile

Available in all colors

Nominal (in)	Actual (in)	Thickness (in)	Grout Joint (in)	Finish
2 x 6	1-13/16 x 5-13/16	3/8	3/16	UPS
12 x 24	11-13/16 x 23-13/16	3/8	3/16	UPS

All field tile is calibrated (non-rectified).  
Crossville recommends a minimum 3/16" grout joint.


#### Coordinating Trim

Available in all colors

Nominal (in)	Actual (in)	Thickness (in)	Grout Joint (in)	Finish
4 x 24 Single Bullnose	3-13/16 x 23-13/16	3/8	3/16	UPS
6 x 12 Cove Base	5-7/8 x 11-3/4	3/8	3/16	UPS



4 x 24 Single Bullnose



6 x 12 Cove Base  
(universal flat top)

### Product Performance

Breaking Strength	≥400 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.50%	ASTM C373
Scratch Hardness	7	Mohs Scale

### Wet Dynamic Coefficient of Friction Range

UPS	.50 – .60	ANSI A326.3
-----	-----------	-------------

### Shade & Texture Index

Gotham® has a shade variation of V2.

V1	V2	V3	V4	V1 Uniform appearance
				<b>V2 Slight Variation</b>
				V3 Moderate Variation
				V4 Substantial Variation

This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

### Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



### Application Areas

Finish	Interior Floors (dry)	Interior Walls (wet/dry)	Exterior Walls	Interior Floors (Standing water/shower floors)	Exterior/Paving	Pool/Fountain Full Lining**	Water Line Pool/Fountains
UPS	✓	✓	✓			✓	✓

\*\* Excludes mesh mounted mosaics. Crossville recommends face mounted or edge mounted mosaics for fully submerged applications. Contact your Crossville sales representative for more information.

NOTE: Trim applications will differ from field tile applications for the same series.

For more information on ANSI-A362.3 visit our website at <https://www.crossvilleinc.com/Resources/Tile-101/DCOF?tab=1>

