Main Street Porcelain Stone®

# Distinctly American. Uniquely Crossville.



### Color Palette

#### Colors







AV211 ▶ Cinema Champagne

AV212 Café Caramel

AV213 ► Bistro Brown



AV214 ► Gallery Grey



AV215 ► Boutique Black



## Specifications

**Sizes** Available in all colors





#### Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment.



#### Sizes & Finishes

Field Tile			
Nominal (in)	Actual (in)	Thickness (in)	Finish
6 x 6	5-13/16 x 5-13/16	3/8	UPS
6 x 18	5-13/16 x 17-13/16	3/8	UPS
12 x 12	11-13/16 x 11-13/16	3/8	UPS
18 x 18	17-13/16 x 17-13/16	3/8	UPS

Crossville recommends a grout joint of 3/16 " to 1/4 "

Actual measurements stated in inches indicate tile is calibrated (non-rectified).

Actual measurements stated in mm indicated tile is rectified.

Mosaics			Available in all colors	
Nominal (in)	Actual (in)		Thickness (in)	Finish
2 x 2 Mosiacs*	1-13/16 x 1-13/1	.6	3/8	UPS

Mesh mounted on a 11-13/16 x 11-13/16 in sheet.

Coordinating Trim			
Nominal (in)	Actual (in)	Thickness (in)	Finish
4 x 12 Single Bullnose	3-3/4 x 11-3/4	3/8	UPS
6 x 12 Cove Base	5-7/8 x 11-3/4	3/8	UPS
		n	

4 x 12 Bullnose 6 x 12 Cove Base

Product Performance		
Breaking Strength	>500 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.10%	ASTM C373
Scratch Hardness	7	Mohs Scale

#### Wet Dynamic Coefficient of Friction

UPS	0.66 - 0.76	AcuTest <sup>™</sup>

#### Shade & Texture Index

Main Street has a shade variation of V3.



This porcelain tile product is produced with a V3 variation. Expect that the amount of color and texture on each piece may vary significantly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.

#### Recommended Use

Main Street is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. Main Street is not recommended for exterior horizontal surfaces or exterior paving. If offset pattern is required for tiles 15 inches or longer, Crossville® recommends an offset of not greater than 33%. f an offset greater than 33% is specified, specifier and owner must approve mock-up and lippage. See CrossvilleInc.com for detailed installation instructions.

#### Environmentally Conscious

Main Streetis made using Crossville's EcoCycle Tile Process<sup>™</sup>, it contains a minimum 4 percent pre-consumer third-party recycled content and is Green Squared<sup>®</sup> Certified. Through these recycling processes Crossville recycles nearly 12 million pounds of previously discarded filtrate and fired tile waste. In addition to its own fired waste recycling, Crossville also accepts and recycles reclaimed, previously installed tile through its Tile Take-Back<sup>™</sup> Program. For more information, visit CrossvilleInc.com/green.

#### Wet Area Use Mainstreet Mosaics

Crossville® produces the Main Street mosaics with the Cross-Sheen® (UPS) finish. The AcuTest<sup>sm</sup> Wet Dynamic COF of the Main Street UPS finish is + .60. Their small sizes ensure frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning. This information is provided so that customers may make a realistic and informed decision when comparing Main Street to other tile products in wet area environments. such as residential/commercial bathrooms, showers, and interior pool deck

#### **Care and Maintenance**

Regular cleaning is the best way to keep Main Street tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville® products is available at CrossvilleInc.com.

#### Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1- 2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.



#### CrossvilleInc.com

If you want a better idea of what Crossville tile would look like in a particular room setting, simply visit our website and click on Cross-Vision. This powerful software tool allows you to visualize different types of Crossville tile. In addition, you'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general, please visit us at CrossvilleInc.com.

#### Hydrotect

Our porcelain tiles are available with Hydrotect. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defense against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. For complete details check our website at CrossvilleInc.com.

WHYDROTECT

Trade Organizations















## Main Street Porcelain Stone®

A city-inspired product that combines function and durability with the beauty of Crossville Porcelain Stone. Main Street is a contemporary line from Crossville that promises to be a commercial favorite.

- Contemporary color palette
- Neutral colors enhanced by
- subtle stone look
  Extremely durable for longlasting beauty
- High DCOF and low maintenance ideal for commercial settings
- Crossville recommends a grout joint of 3/16 to 1/4 inch





AV212 ► Café Caramel 18 x 18

Main	Street		

Crossville, Inc.

PO Box 1168 Crossville, TN 38557 Phone931.484.2110Fax931.456.2956E-MailCrossc@CrossvilleInc.comWebCrossvilleInc.com

