

LAGUNA

PORCELAIN TILES



LAGUNA 2x8

PORCELAIN TILES

Laguna White



5 x 20 cm | 2" x 8"
GLOSSY

Laguna Shell



5 x 20 cm | 2" x 8"
GLOSSY

Laguna Beige



5 x 20 cm | 2" x 8"
GLOSSY

Laguna Blue



5 x 20 cm | 2" x 8"
GLOSSY

Laguna Green



5 x 20 cm | 2" x 8"
GLOSSY

Laguna Brown



5 x 20 cm | 2" x 8"
GLOSSY

Laguna Black



5 x 20 cm | 2" x 8"
GLOSSY

*Cover: Laguna Brown
& Laguna Beige*



LAGUNA 2x8
PORCELAIN TILES

PRODUCT INFORMATION

	Product	Finish	Rectified	Unit	Work Size	Thick	Faces	Sq. Ft/ Carton	Pieces/ Carton
	Wall 2"x8"	Glossy	No	SF	2.25" x 8" 5.65 cm x 20.26 cm	9.5 mm	46	4.43	36

USAGE RECOMMENDATION

Walls & Countertops	Target DCOF	Residential	Commercial
Indoor Walls / Backsplash / Shower walls (Wet)	N/A	✓	✓
Indoor Walls (Dry)	N/A	✓	✓
Outdoor Walls (Covered)	N/A	✓	✓
Outdoor Facades (Uncovered)	N/A	✓	✓
Countertops	N/A	✓	✓

Floors & Traffic Areas	Target DCOF	Residential	Commercial
Indoor Floors Level (Wet / Shower Floors)	≥ 0.42	—	—
Indoor Floors Level (Dry)	N/A	✓	✓
Outdoor Floors Level (Covered)	N/A	—	—
Outdoor Floors Level (Uncovered)	≥ 0.60	—	—
Indoor & Outdoor Ramps / Inclines	≥ 0.65	—	—

Pools & Water Features	Suitable
Pool Waterline	✓
Interior Pool Walls	✓
Pool Floors / Submerged Steps	—
Pool Deck	—
Hot Tub Walls	✓
Hot Tub Floors / Steps	—
Hot Tub Deck	—
Sauna Walls	✓
Sauna Floors	—

Specialty Applications	Suitable
Fireplace Surround	✓
Fireplace Hearth	—
Commercial Kitchen Walls	✓
Commercial Kitchen Floors	—

A DCOF value of ≥ 0.42 is the standard for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-A326.3.

INSTALLATION AND CARE

Grout Joint Recommendation 1/16"
Shade Variation V4

Professional tile installation is recommended. For complete installation instructions consult the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation. Follow the grout manufacturer instructions for the complete removal of grout and construction residue from initial installation.

Eliane recommends using a cloth with water and a neutral cleaner (soap-less) or a general household cleaner for tiles cleaning.

PERFORMANCE CHARACTERISTICS

	ASTM #	Result
Water Absorption	C373	≤ 0.5%
Breaking Strength	C648	≥ 275 lbf
DCOF WET	ANSI A137.1 ANSI A326.3	< 0.42
Scratch Hardness	MOHS	6
Frost Resistance	C1026	Yes
Stain Resistance	C1378	Resistant
Chemical Resistance	C650	Resistant

SUSTAINABILITY



Eliane ceramic and porcelain tiles are low-emitting materials with zero emission of volatile organic compounds (VOC).



Recycled Content:
4.7% Pre-consumer
1.5% Post-consumer

QUALITY CARE



Standard quality tiles manufactured by Eliane Ceramic Tiles meet ISO 13006, ANSI A137.1 standards.



Eliane ceramic and porcelain tiles are NOT flammable, except mesh material of mesh mounted mosaics.



Laguna Beige and Laguna White 2x8



Laguna Blue 2x8



Laguna Green 2x8



Laguna White 2x8



Laguna Black 2x8



Laguna Shell 2x8





Laguna Black 2x8



Laguna Shell 2x8



Laguna Green 2x8



Laguna Blue 2x8