Specifications

Sizes Shown in SHD46 Haze SO)



Field Tile			Available in all colors	
Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
6 x 24	147 x 597	9.5	3	UPS/SPO
12 x 12 Triangle	297 x 297	9.5	3	UPS
12 x 24	297 x 597	9.5	3	UPS/SPO/PTN
24 x 24	597 x 597	9.5	3	UPS/SPO
24 x 48	597 x 1197	10.5	3	UPS/SPO

Note: All field tile is rectified with a 3mm grout joint.

Mosaic				
Nominal (in)	Actual (mm)	Sheet (mm)	Thickness (mm)	Finish
1 x 3 Blended Mosaics	22 x 72	297 x 297	9.5	SPO
2 x 2 Solid Mosaics	47 x 47	298 x 298	9.5	UPS
14 0 1 1				

 $\dagger\,1$ x 3 mosaics mesh mounted in 11-7/8 x 11-7/8 sheets with 3mm grout joints.

Coordinating Trim				
Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
4 x 24 Single Bullnose	96 x 597	9.5	3	UPS/SPO
6 x 12 Cove Base	150 x 297	9.5	3	UPS

6 x 12 Cove Base

12	Х	24	

24 x 24



12 x 12

Triangle



Mosaics UPS

2 x 2 Solid 1 x 3 Blended Mosaics (SHD4 Shown)

Wet Dynamic Coefficient of Friction Range

UPS 0.50 - 0.60 AcuTest sm	
SPO 0.42 - 0.52 AcuTestsm	
PTN 0.42 - 0.52 AcuTest™	

7

500 lbf

>200 psi

Unaffected

Resistant

<0.30%

Shade & Texture Index

4 x 24 Single Bullnose

Bond Strength

Frost Resistance

Water Absorption

Scratch Hardness

Product Performance Breaking Strength

Chemical Resistance

Shades by Crossville[™] has a shade variation of V2.



V2 Slight Variation V4 Substantial Variation

ASTM C648

ASTM C482

ASTM C650

ASTM C1026

ASTM C373

Mohs Scale



Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.

