Moonstruck Porcelain Stone®

Sizes (Available in all colors)







AV305 ▶ Apollo 12 x 24 HON

Sizes & Finishes

4	Fleia I IIe			
	Nominal (in)	Actual (mm)	Thickness (mm)	Finish
	12 x 24	297 x 597	10.5	UPS/HON
	18 x 36	447 x 897	10.5	UPS/HON

Crossville recommends a grout joint of 3mm

Actual measurements stated in inches indicate tile is calibrated (non-rectified)

Coordinating Trim

Nominal (in)	Actual (mm)	Thickness (mm)	Finish
4 x 24 Single Bullnose	96 x 597	10.5	UPS/HON



4 x 24 Single Bullnose


Product Performance		
Breaking Strength	>500 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.20%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

UPS	0.50 - 0.60	AcuTestsm
HON	0.42 - 0.52	AcuTestsm

Shade & Texture Index

Moonstruck has a shade variation of V3.



V1 Uniform appearance V2 Slight Variation

V3 Moderate Variation

This porcelain tile product is produced with a V3 variation. Expect that the amount of color and texture on each piece may vary significantly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation

Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



