

Craft

COLOURED-BODY GLAZED STONEWARE

INTENDED USE: NATURAL   ANTI-SLIP

QUILT




 9 mm

 9 mm


 9 mm

DECOS



MOSAIC BASKET WEAVE
QUILT
NATURAL
24x24 Rect - 30x30 cm
 9 mm



HERRINGBONE MODULUS A-B
QUILT
NATURAL
10"x24" Rect - 24x60 cm
 9 mm

P R () T E C T

ANTIMICROBIAL SURFACE
with **HydroBant[®]**

TRIM PIECES



BULLNOSE
3"⁸"x12" Rect - 8x30 cm
NATURAL
 9 mm
All colors available



COVE BASE
6"x12" - 15x30 cm
NATURAL
 9 mm
Special order only

Craft















COLOURED-BODY GLAZED STONEWARE

P R () T E C T

ANTIMICROBIAL SURFACE
with **HydroBant[®]**

TECHNICAL FEATURES

COLOURED-BODY GLAZED STONEWARE according to ANSI A137.1 (Glazed Porcelain Tiles - P1 Class)

TECHNICAL FEATURES	TEST METHOD	REQUIRED VALUES	CONFORMS
 WATER ABSORPTION	ASTM C373	≤ 0.5%	CONFORMS
 BREAKING STRENGTH	ASTM C648	≥ 250 lbf	350 lbf @ 9 mm
 PEI	ASTM C1027	As indicated by manufacturer	PEI 5: COTTON, WAX, ROPE, WOOL PEI 4: OIL
 LINEAR THERMAL EXPANSION	ASTM C372	No provision	$\alpha \leq 4.4 \times 10^{-6} \text{ } ^\circ\text{F}^{-1}$ $\alpha \leq 8 \times 10^{-6} \text{ } ^\circ\text{C}^{-1}$
 STAIN RESISTANCE	ASTM C1378	As indicated by manufacturer	A RESISTANT
 CHEMICAL RESISTANCE ^(*)	ASTM C650	As indicated by manufacturer	A RESISTANT
 FROST RESISTANCE	ASTM C1026	As indicated by manufacturer	RESISTANT
 BOND STRENGTH	ASTM C482	≥ 50 PSI	CONFORMS
 SLIP RESISTANCE	DIN EN 13035 - Annex B DIN EN 13035 - Annex A ANSI A328.3	-	R11 Anti-Slip*** C (A4-B4) Anti-Slip**** ID - DCOF ≥ 0.42 (dry) Natural IW - DCOF ≥ 0.42 (wet) Natural EW Anti-Slip****
 SHADE VARIATION	ANSI A137.1	As indicated by manufacturer	V2 Slight variation
 FLAME SPREAD	ASTM E84	-	Class A
 THERMAL CONDUCTIVITY	EN 12524	-	$\lambda = 1.3 \text{ W/m } ^\circ\text{K, 0.7 BTU/in } ^\circ\text{F}$
 RECOMMENDED MINIMUM JOINT ^(*)	RECT (INDOOR) OUTDOOR	-	1/8" - 3.2 mm approx. 3/16" - 4.7 mm approx.
 THICKNESS	SIZES	-	9 mm 24"x24" Rect - 60x60 cm 12"x24" Rect - 30x60 cm 8"x24" Rect - 20x60 cm

(*) Excluding hydrofluoric acid and its derivatives.

(*) Joint Recommendations: Per TCMA Handbook, the minimum required joint width for ceramic tile and natural stone is 1/16". Sealing ceramic or stone without a grout joint of a least 1/16", often referred to as a "dry" joint, is not recommended. For outdoor applications, the minimum required joint width is 1/8". For applications in public showers, locker rooms and steam rooms, for which an Anti-Slip surface is recommended, the minimum required joint width is 3/16".

(**) With the exception of areas characterized by a higher risk of slipping (such as public showers, locker rooms and steam rooms) for which an Anti-Slip surface is recommended.

(***) Anti-Slip surface special order only.

PACKINGS AND WEIGHTS

SIZES	SF / CTN	LINEAR FT / CTN	PIECES / CTN	CTN / PALLET	SF / PALLET	LBS / CTN	LBS / PALLET
24"x24" Rect Natural / Anti-Slip	15.61	-	4	36	501.96	64.49	2,324.63
12"x24" Rect Natural / Anti-Slip	15.61	-	8	32	499.45	64.48	2,063.38
8"x24" Rect Natural / Anti-Slip	11.95	-	9	36	492.20	48.28	1,737.89
MOSAIC BASKET WEAVE 12"x12" Rect Natural	4.84	-	5	90	435.00	19.40	1,746.06
HERRINGBONE MODULUS A-B 10"x24" Rect Natural	5.54	-	6	35	193.90	24.91	872
COVE BASE 6"x12" Natural	3.67	-	8	108	417.96	16.53	1,782.24
BULLNOSE 3"x12" Rect Natural	5.17	19.69	20	112	579.04	19.84	2,222.88

* No antimicrobial protection