



PRODUCT SPECS



12"x24"

Piece Size: 11.81"x23.62"
 Thickness: 9 mm
 Material: Porcelain
 Faces: 16



24"x48"

Piece Size: 23.66"x47.24"
 Thickness: 9 mm
 Material: Porcelain
 Faces: 4

	PCS/BOX	PCS/PALLET	BOXES/PALLET	BOX WEIGHT (LBS)	PALLET WEIGHT (LBS)	SQFT/PCS	SQFT/BOX	SQFT/PALLET
12"x24"	6	240	40	43.68	1747	1.937	11.622	464.88
24"x48"	2	72	36	63.48	2285	7.75	15.5	558

	Standard	Result
Scratch Resistance (MOHS)	MOH's Scale	Min. 7
Coefficient of Friction (DCOF)	ANSI A326.3	≥ 0.42
Deep Abrasion	ASTM C1243	Unglazed: Max 175mm
Color Uniformity	ASTM C609 and Section 9.3	Max. 3 Judds
Water Absorption	ASTM C373	Wa ≤ 0.5%
Breaking Strength	ASTM C648	Average ≥ J275 lbf. (1.22 kN)
Resistance to Freeze /Thaw Cycling	ASTM C1026	Pass
Shade and Texture Rating	-	V3

Interior Wall Interior Floor Backsplash Shower Floors Shower/Wet Areas Fireplace Surrounds Exterior Wall Exterior Floor Pool/Fountain



Application - Residential/Commercial

Recommended uses only apply for properly installed material according to TCNA guidelines. All information is subject to change; refer to the website for most updated information. Images were digitally enhanced; for color accuracy, please request a sample.

IMPORTANT: Installation Instructions

We recommend wet cutting or the score and snap method during the installation process. Improper installation techniques could expose installer to harmful silica dust.

Do not dry cut product using power tools during the installation process. Using dry cutting methods could present a risk of acute lung injury. If adequate ventilation cannot be achieved, wear a mask or respirator. For more information, see the SDS at <https://anthologytile.com>