

Lunada Bay Tile is pleased to partner with Tommy Bahama to create an exquisite collection of glass mosaic blends inspired by the most exotic and untouched destinations of the world. Whether you're designing a spa, a backdrop for gatherings, or your most intimate spaces at home, Tommy Bahama encourages us to live spontaneously, unwind in style, and to feel our very best.



Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.



Up To 70%
Post-Consumer
Recycled Content

© 2022 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE		FLOOR APPLICATIONS		
Application	Suitable		Interior	Exterior
Interior Wall/Backsplash	Yes	Shower	Yes	Yes
Fireplace/Cooktop Surround	Yes *	Steam Shower	Yes **	N/A
Shower Wall	Yes	Light Residential	Yes	No
Steam Shower	Yes	Residential	No	No
Exterior Wall	Yes	DCOF Value of ≥ 0.42 is accepted value for use in commercial applications. A 137.1-2018		
Pool, Spa or Water Feature (fully submerged)	Yes **			

PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage (SF Per Sheet)	Packaging (Per Box)			
1 x 1" Offset	1.07	5 Sheets/5.35 SF	Breaking Strength	ASTM C-648	> 350 PSI
1 x 2" Brick	1.00	5 Sheets/5.00 SF	Water Absorption	ASTM C-373	Impervious < 0.5%
1/2 x 4" Brick	0.84	5 Sheets/4.20 SF	Chemical Resistance	ASTM C-650	Unaffected
1 x 4" Brick	0.85	5 Sheets/4.25 SF	Freeze/Thaw	ASTM C-1026	Unaffected
Vineyard	0.82	5 Sheets/4.10 SF	Thermal Shock	ASTM C-484	Passed
Zig & Zag	0.74	5 Sheets/3.70 SF			

Shade Variation	Grout Joint Recommendation
V4 - Substantial Variation	1/16" (1.6 mm)

NOTES

Since variations are common in artistic glass tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. **Installation constitutes acceptance.** We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).

MAINTENANCE

A routine cleaning of Tommy Bahama Glass tiles can be done with light duty, diluted close to neutral pH cleaner.

* Acceptable for use near open flame or heat source; however, it is not considered 'Fire Glass'.
 ** ACCEPTABLE SIZES: 1 x 1", 1 x 2", and Vineyard Only. No other sizes are recommended.

FLOOR APPLICATION DEFINITIONS:
Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.
Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.