Technical Data Sheet

MDF WOODGRIP

High performance synthetic resin adhesive

DESCRIPTION

Specially formulated to provide good adhesion to medium density fibreboard

ADVANTAGES

- Easy to use
- Ideal for medium density fibreboard (craft wood)
- Can be applied by gun, squeeze bottle or glue spreader

PROPERTIES

Appearance	An apricot syrupy liquid
Viscosity	1500 – 3000 CPS 4/20/25
Solids	Approx. 53%
Specific Gravity	Approx. 1.06
Initial Tack	Medium – develops fast tack
Set speed	Fast

APPLICATION INSTRUCTIONS

Surfaces to be bonded should be clean and dry and free of grease and oil. It is recommended that light sanding be done before gluing. Joints to be bonded should be close fitting. Timber and moisture content should be in the range of 7-10%. Adhesive may be applied by brush, roller or squeeze bottle. When practical apply to both surfaces of the joint. Recommended spread rate is 3-5M_2 of glue line per litre.

STORAGE

12 to 18 months in a dry cool place in original container.

PACKAGING

Squeeze bottle	500ml.
Jerry type	4 Litre, 20 Litre

PRECAUTIONS – HEALTH AND SAFETY

Considered to be practically non harmful.
Repeated and prolonged contact with skin may result in irritation and dermatitis effects.
May be an irritant to eyes.
Inhalation of any spray mist may cause irritation to respiratory tract
Ingestion may cause nausea and vomiting.
Seek medical advice for a doctor or poisons information centre if any of the above occurs.

NOTE

Safety Data sheets for these and all AFTEK products are available on request. Read the SDS and product label carefully before using.
All reasonable care is taking in the compilation of this data sheet. All recommendations regarding the use are made without guarantee as the conditions of use are beyond the control of the manufacturer.

The information and any recommendations relating to the application and end-use of all IAFTEK products are provided in good faith based on AFTEK's knowledge and experience of the products. In applications, the differences in materials, and variances of substrates and actual site conditions can vary such that no warranty in respect of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be taken as inferred either from this information, or from any written recommendations, or from any other advice offered by AFTEK. The proprietary rights of third parties must be observed. All orders are accepted subject to our sale terms and conditions. All users should always refer to the most recent and up to date issue of the Technical Data Sheet for the product concerned, which is available on request. It is recommended that products should always be properly stored, handled and applied under tested and recommended conditions. PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.