

ENSEAL CLEAR

TREATED PINE “CUT END” SEALER



DESCRIPTION:

RLA ENSEAL CLEAR is a transparent resealing solution designed for use on pressure treated timber in above ground applications where cutting, notching, drilling, machining or other work exposes areas of unpenetrated wood.

USES

- For resealing of treated timber products where cutting to length, rebating, notching, drilling or other work during installation or fitting exposes fresh timber surfaces
- Suitable for timber surfaces that are above ground as in H2 and H3 situations*

***Important:** cut end must not be placed in ground contact

APPLICATION:

- Ensure adequate ventilation during use and avoid inhaling spray mist
- Shake can briefly before use
- The timber surfaces to be resealed should be dry and clean
- Turn spray tip so that the arrow on the nozzle points towards the surface to be sprayed
- Hold can 15 to 20 cm from the timber surface and apply the product liberally onto the freshly exposed surface until the solution ceases to absorb readily and just starts to run on the surface

COVERAGE

Coverage up to 2m² per can depending on wood condition and grain orientation (end grain will be most absorbent).

PAINTING OVER:

- Refer to AS1604 for requirements
- Allow treated surfaces to dry for a minimum of 48 hours prior to painting over
- Seek paint manufacturers advice for sealing treated ends with oil based primers / finishes, as timber treated with Enseal is susceptible to leaching and discoloration through finishes

LIMITATIONS

- Enseal Clear is only for supplementary use on treated wood products that have been preservative treated in accordance with AS1604
- This product is not suitable for application to, or protection of untreated timber
- Do not use for any other purpose
- Use of this or an equivalent product is recommended in order to conform with manufacturers guarantees on treated wood products

SHELF LIFE/STORAGE:

- Store in a cool, secure place
- Protect from sunlight and do not expose to temperatures exceeding 50°C.
- Keep out of reach of children.
- Enseal is best used within 12 months from date of manufacture when stored in the above conditions in the original unopened container.

CONTAINER SIZES:

300g aerosol cans

WARNING:

- Intentional misuse by deliberately inhaling contents can be harmful or fatal
- Do not puncture the container even when empty
- Avoid breathing vapour and mist
- Provide adequate ventilation when spraying in confined spaces
- Avoid contact with eyes and skin

HEALTH AND SAFETY:

For information and advice on the safe handling, first aid, storage and disposal of chemical products, users must refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

PRODUCT INFORMATION:	
Form	White Spirits based solution in pressurised container
Ingredients	26 g/kg (20 g/L) zinc (Zn) present as zinc naphthenate. 1.3 g/kg (1 g/L) permethrin 880 g/kg liquid hydrocarbons
Propellant	Hydrocarbon

WARRANTY STATEMENT:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.

We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.

RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with relevant Australian Standards.

Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.

Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.

The consumer is responsible for any expenses incurred in making a claim.

A claim form can be requested by:

PHONE: 1800 242 931

EMAIL: info@rlapolymers.com.au

MAIL: 215 Colchester Road Kilsyth Victoria 3137
(Attention Customer Service)

WEBSITE: www.rlapolymers.com.au

AUSTRALIAN CONSUMER LAW:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

DISCLAIMER:

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.

Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

Version: 01

Issue date: 27/09/2024

RLA Polymers Pty Ltd ACN 004 709 915

Head Office
215 Colchester Road
Kilsyth, Victoria, 3137
Tel: 1800 242 931

New South Wales
5A 246 Miller Road
Villawood, NSW, 2163

Queensland
57 Fulcrum Street
Richlands, QLD, 4077

South Australia
Unit 2/7 Berger Road
Wingfield, SA, 5013

Western Australia
24 Hanwell Way
Bassendean, W.A, 6054
Tel: 08 9279 8911

For the latest product information please visit rlapolymers.com.au