ROBERTS European Technology, Locally Made.

TDS Technical Data Sheet

ROBERTS R6150
Spray Contact Adhesive



DESCRIPTION:
ROBERTS R6150 Sprayable contact adhesive is a high-quality solvent-based contact adhesive designed for easy application by spraying to bond a wide range of materials. It has excellent bond strength and high heat resistance. The high solids content gives outstanding economy of use.
NOT RECOMMENDED FOR EXTERIOR APPLICATION.

RECOMMENDED USE:
ROBERTS R6150 Sprayable Contact Adhesive is designed for use on most types of

- Vinyls,
- PVC skirtings/ extrusions,
- Cover strips,
- Plastic
- Metal treads nosing
- Decorative laminates
- MDF
- Wood
- Wood veneers
- Timber.
- Plasterboard (Gyprock)
- Concrete
- Paper honeycomb

And most common, Building substrates.

COVERAGE:
6-8m^2 per litre
Spread rates may vary depending on the condition and substrate absorbency.

CONTAINER SIZES:
20-litre

SHELF LIFE / STORAGE:
Keep the container tightly closed. Store Locked up. Keep the container in a cool, well-ventilated place away from heat sources.

SURFACE PREPARATION:
To be by the current Australian Standard "Floor Coverings 1884-2021 Resilient Sheet & Tiles – Laying & Maintenance Practices."
All surfaces should be dry, smooth, sound, clean and free of wax, grease, oil, previously applied adhesive, and other contaminants.
Priming is only generally required when installed on Highly porous subfloors,
If priming is required, use *Roberts R48 Universal Primer.*

APPLICATION:
ROBERTS R6150 Sprayable is designed for all conventional solvent spray equipment using suction feed or pressure pot equipment. A recommended minimum pressure of 30psi is required to give optimum bond strength. Alternatively, the application can be by way of a roller or brush. An even coating should be applied to both surfaces, ensuring complete coverage and the adhesive allowed to dry before bonding. On absorbent materials such as polyurethane foam, bonding can be achieved within minutes of application, depending on atmospheric conditions. On less porous materials such as laminates, MDF, and wood veneer, open time can be up 10-15 minutes, depending on atmospheric conditions.
Use sufficient pressure to ensure 100% contact is recommended in all cases.
Wear full protective clothing and self-contained breathing apparatus.

CLEAN UP:
Use ROBERTS R900 Cleaner (Highly Flammable) to clean up equipment and adhesive spills. ROBERTS R900 is not recommended for removing adhesive from vinyl, carpet, or painted surfaces.

HIGHLY FLAMMABLE:
Contains 30-60% Liquid Hydrocarbons

FIRE:
In the case of FIRE, use foam to extinguish.
Firefighters should

SAFETY & HANDLING:

KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES – NO SMOKING

- Ground/bond container and receiving equipment.
- Use explosion-proof electrical /ventilation/lighting equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharges.
- Keep the container tightly closed.
- Wear suitable respiratory protection.
- Use in well-ventilated areas.
- Avoid breathing vapours
- Persons who are sensitive to odours and chemicals should avoid the work area.
- Avoid contact with skin and eyes.
- Wear eye protection and suitable gloves and clothing.
- Do not eat, drink, or smoke while using this product.
- If on the skin, wash with plenty of soap and water.
- If in the eyes: rinse cautiously with water for several minutes.
- Remove contact lenses; if present, continue rinsing.
- If any skin or eye irritation persists or you feel unwell, get medical attention.

FIRST AID:

If poisoning occurs, contact a doctor or Poisons Information Centre.
Skin: Wash off with warm water and soap.
If swallowed, DO NOT induce vomiting. Give a glass of water.
For advice or if you feel unwell, contact a Poisons Information Centre: Australia ph. 131126,
New Zealand ph. 0800 764 766 or a doctor at once.
If swallowed, do NOT induce vomiting.
If SWALLOWED, immediately call the Poisons Information Centre or a doctor.
If ON SKIN, Remove immediately all contaminated clothing and wash skin with soap and water.
If skin irritation occurs, get medical advice/attention.
IF IN EYES Rinse carefully with water for several minutes.
If eye irritation persists, get medical advice/attention.
The Safety Data Sheet is available upon request.

WARRANTY STATEMENT:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specifications.
We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.
RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out per the relevant Australian Standard, the Floorcovering Manufacturer's instructions, and the floorcoverings must be subject to normal traffic conditions.
Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.
Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.
The consumer is responsible for any expenses incurred in making a claim.
A claim form can be requested by:

PHONE: 1800 242 931
EMAIL: info@rlapolymers.com.au
MAIL: 215 Colchester Road Kilsyth Victoria 3137 (Attention Customer Service)
WEBSITE: www.rlapolymers.com.au

AUSTRALIAN CONSUMER LAW:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

DISCLAIMER:

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.
Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.