ROBERTS

ROBERTS 679

Carpet Latex Adhesive



DESCRIPTION:

ROBERTS R679 Carpet Latex is a compounded latex product used for the sealing of raw edges, strengthening worn backing, replacing damaged nap, and adhering pad underlays to subfloors

BONDING APPLICATION:

DOMESTIC UNDERLAYS:

Apply a liberal amount of latex to a dry, clean, sound, and smooth substrate.

Place underlay into the wet latex and install underlays according to manufacturers' recommendations.

SEALING SELVEDGE:

Before Heat Bond Seaming, most tufted and woven carpets are prone to lose tufts or unravel after the selvedge is trimmed

It is recommended that Carpet Latex be applied to the edge of the seam before Head Bond Seaming

Work latex into the edge and allow it to dry before seaming

WORN BACKING:

Lay the carpet face down.

Apply a liberal amount of latex to the carpet backing with a brush or roller to the areas that need attention to ensure a good bond.

Allow the carpet to dry in position for 4-5 hours

CLEAN UP:

Clean tools immediately after use with water. The dried adhesive may be cleaned off using ROBERTS R550 Latex/Acrylic Adhesive Remover applied to a damp cloth, then rubbed gently over the dried adhesive or with RLA Handy Wipes.

SHELF LIFE / STORAGE:

12 months when stored in original unopened packaging shall be stored in a dry area off the ground

PACKAGING:

1litre and 5litre bottles

15litre pails

HEALTH & SAFETY:

For information and advice on the safe handling, first aid, storage and disposal of chemical products, users must refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

WARRANTY STATEMENT:

RLA Polymers guarantees this product against manufacturing defects and guarantees it to be manufactured to our published specification.
We certify that this product is suitable for use when fully cured and will perform as described in our technical data sheet or other published materials.
RLA Polymers will replace the product free of charge when purchased from any legally verifiable source and where a product is proven to have been stored, handled, and install according to instructions published on our packaging and within the stated shelf life. The Installation of all materials must be carried out in accordance with relevant Australian Standards.
Warranty doesn't apply if damage, loss, failure to follow instructions, or other circumstances are out of our control.
Sufficient time and access to investigate any complaint must be accorded to RLA Polymers.
The consumer is responsible for any expenses incurred in making a claim.
A claim form can be requested by:

PHONE: 1800 242 931
EMAIL: info@rlapolymers.com.au
MAIL: 215 Colchester Road Kilsyth Victoria 3137 (Attention Customer Service)
WEBSITE: www.rlapolymers.com.au

AUSTRALIAN CONSUMER LAW:

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality, and the failure does not amount to a major failure. The benefits under our warranty are in addition to other rights and remedies available to the consumer under the law in relation to the goods and services to which the warranty relates.

DISCLAIMER:

All statements and technical information contained herein are based on tests we believe to be reliable, but the accuracy thereof is not guaranteed.
Users assume all risk and liability resulting from the use of the product and must confirm the suitability thereof by their own tests. Conditions of Sale contain a limited warranty against manufacturing defects.

RLA Polymers Pty Ltd ACN 004 709 915

Head Office
215 Colchester Road
Kilsyth, Victoria, 3137
Tel: 1800 242 931

New South Wales
5A 246 Miller Road
Villawood, NSW, 2163

Queensland
57 Fulcrum Street
Richlands, QLD, 4077

South Australia
Unit 2/7 Berger Road
Wingfield ,SA, 5013

Western Australia
24 Hanwell Way
Bassendean, W.A, 6054
Tel: 08 9279 8911