

# Domtar POS 55H - 2.4

## Product Specifications

Caliper (mils/ μm)	Basis Weight	Brightness (UV Included)	Thermal Response - Nominal				Gurley Stiffness Nominal (mg)		Elmendorf Tear Nominal (g)		Parker Print Surf
			Static - (°C ± 5°)		Dynamic - Atlantek 400 (mJ/mm <sup>2</sup> )		MD:	CD:	MD:	CD:	
			0.2 ODU	87	0.2 ODU	4.6					
2.4 /61	17 x 22— 500 (lbs)	>85	0.2 ODU	87	0.2 ODU	4.6	28	15	31	35	<1.90
	13.9		1.0 ODU	134	1.0 ODU	7.9					
	g/m <sup>2</sup>		Max. Density	1.38	Max. Density	1.78					
	52.2		Required Temp.	149	Energy Req.	14.6					

### Features:

- High sensitivity
- Excellent graphics and bar code imaging
- Bright white appearance
- Flexographic printable front and back
- Lithographic printable back side only

### Ideal For:

- Point-of-sale receipts
- ATM receipts
- Kiosks
- Parking receipts
- Airline check-in kiosks
- High speed facsimile
- Charting
- Portable receipts

### Environmental Characteristics:

- Produced without the use of bisphenol A (BPA)

