LynxJET[®] Dye



Basis Weight	GSM	Brightness GE	Opacity	Smoothness	Caliper	Length Target (+/-200 linear feet) 40"/3"	Length Target (+/-200 linear feet) 50"/3"
BOND 17 x 22							
20/50	75	96	92	130	3.8	26,700	41,500
24/60	90	96	94	130	4.6	22,600	35,000
28/70	105	96	96	130	5.0	19,900	30,800

Features:

- 96 brightness with a true white shade
- Excellent opacity for minimal side to side show-through
- Surface treatment specifically engineered for improved print quality when used on dye based systems - greater lifts in density and depth of color
- Designed for today's most advanced dye high-speed inkjet systems
- · Consistent runnability on press and in post-processing equipment for inserting, punching and folding
- Available in rolls

Environmental Characteristics:



- Forest Stewardship Council® (FSC®) certified by Preferred by Nature
- Sustainable Forestry Initiative® (SFI®) Certified Sourcing
- Made with Elemental Chlorine Free (ECF) virgin fiber content
- · Manufactured under alkaline (acid-free) conditions for increased longevity and performance

Common Uses:

- Direct mail
- Statements
- Transpromotional documents

Electronic Imaging Guarantee:



Domtar's digital and inkjet products are designed and recommended for digital and inkjet production presses, desktop printers (laser and inkjet) and copiers within the limitations specified by the original equipment manufacturer.

We partner with leading OEM's to print test and certify our inkjet products as fit for use on a wide variety of equipment. Domtar's products are optimized for runnability on press and through post-processing. Our surface treatment will enhance print quality compared to untreated stocks when using dye inks. Our products are suitable for offset pre-print. As always, Domtar stands behind our commitment and our products.

