

SECTION 1. PRODUCT IDENTIFICATION

1.1 TRADE NAME (AS LABELED):	VTX 300 Winter Part A
<u>PRODUCT CODE:</u>	N/A
<u>SYNONYMS:</u>	N/A
<u>CAS#:</u>	Mixture
1.2 PRODUCT USE:	Floor Coating
<u>MANUFACTURER'S NAME:</u>	Bayvex Technologies
<u>ADDRESS:</u>	8231 214 th Street W, Lakeville, MN 55044
<u>BUSINESS PHONE #:</u>	1-952-491-0024
<u>EMERGENCY PHONE #:</u>	Infotrac: 1-800-535-5053
<u>DISTRIBUTOR NAME:</u>	Penntek Industrial Coatings
<u>ADDRESS:</u>	7850 Lakeville Blvd., Lakeville, MN 55044
<u>BUSINESS PHONE #:</u>	1-844-290-9364
1.4 EMERGENCY PHONE NUMBERS:	InfoTrac 1-800-535-5053
<u>DATE OF CURRENT REVISION:</u>	October 17, 2026
<u>DATE OF LAST REVISION:</u>	New

SECTION 2. HAZARD IDENTIFICATION**EMERGENCY OVERVIEW:** This product is a clear, slightly amber liquid.**Health Hazards:** May cause an allergic skin reaction.**Flammability Hazards:** This product is a flammable liquid and vapor (classification based on solvent content; flash point not determined).**Reactivity Hazards:** This product is not reactive.**Environmental Hazards:** Harmful to aquatic life with long lasting effects.**2.1 EU LABELING AND CLASSIFICATION:**

This product meets the definition of a hazardous substance or preparation as defined by 29 CFR 1910. 1200 and regulation (EU) No. 2020/878 and regulation (EC) No. 1272/2008

Component(s) Contributing to Classification(s)

See Section 3

2.2 LABEL ELEMENTS**GHS Hazard Symbols**

Signal Word: **Warning**

GHS Hazard Classification(s):

Flammable Liquid Category 3

Skin Sensitizer Category 1

Hazardous to the Aquatic Environment, Chronic Category 3

Hazard Statement(s):

H226: Flammable liquid and Vapor

H317: May cause an allergic skin reaction

H412: Harmful to aquatic life with long lasting effects

Prevention Statement(s):

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233: Keep container tightly closed.

P240: Ground and bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/lighting equipment.

P242: Use non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing vapors or mist.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves, protective clothing and eye or face protection.

Response Statement(s):

P302+P352: IF ON SKIN: Wash with plenty of water.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P370+P378: In case of fire: Use dry chemical, CO₂, water spray or foam to extinguish.

Storage Statement(s):

P403+P235: Store in a well-ventilated place. Keep cool.

Disposal Statement(s):

P501: Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3 OTHER HAZARDS:

HAZARDS NOT OTHERWISE CLASSIFIED: None known.

SECTION 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Hazardous Ingredients:	WT%	CAS#	EINECS #	Hazard Classification
Bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	35 - 50%	136210-32-7	412-060-9	Skin Sensitizer Category 1 (H317), Aquatic Chronic Category 3 (H412)
Polyester Polyurea Resin	30 - 40%	136210-30-5	Not Available	Skin Sensitizer Category 1 (H317), Aquatic Chronic Category 3 (H412)
Proprietary Ingredient 1	10 - 20%	Proprietary	Proprietary	Skin Sensitizer Category 1B (H317), Aquatic Chronic Category 3 (H412)
Propylene Glycol Methyl Ether Acetate	1 - 10%	108-65-6	203-603-9	Flammable Liquid Category 3 (H226), STOT SE Category 3 (H336)
Proprietary Ingredient 2	1 - 5%	Proprietary	Proprietary	Aquatic Chronic Category 2 (H411), Flammable Liquid Category 4 (H227)
Solvent naphtha (petroleum), light aromatic	<1.5%	64742-95-6	265-199-0	Aspiration Toxicity Category 1 (H304), Skin Irritant Category 2 (H315), STOT SE Category 3 (H336), Aquatic Chronic Category 2 (H411) - present below the concentration at which the mixture is classified
2,6-Dimethylheptan-4-one	<0.1%	108-83-8	203-620-1	Flammable Liquid Category 3 (H226), STOT SE Category 3 (H335) - present below the concentration at which the mixture is classified
Any shown as a range is to protect confidentiality or is due to batch variation. There are no additional ingredients present which are classified as hazardous to health and require reporting in this section.				

4. FIRST-AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES:

EYE CONTACT: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists.

SKIN CONTACT: Flush contaminated skin with plenty of soap and water. Remove contaminated clothing and shoes. Get medical attention if skin irritation or rash develops. Wash clothing before reuse. Clean shoes thoroughly before reuse.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist or breathing is difficult, get medical attention.

INGESTION: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing skin sensitization or allergic skin conditions may be aggravated by exposure.

4.2 SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

May cause an allergic skin reaction (redness, itching, rash). Repeated or prolonged skin contact may cause sensitization in susceptible individuals. High vapor concentrations may irritate the eyes, nose and throat.

4.3 RECOMMENDATIONS TO PHYSICIANS:

Treat symptomatically. Treat skin sensitization reactions as allergic contact dermatitis. Contact poison treatment specialist if large quantities have been ingested or inhaled.

SECTION 5. FIRE-FIGHTING MEASURES

5.1 FIRE EXTINGUISHING MATERIALS:

Use fire extinguishing methods below:

Water Spray: Yes

Carbon Dioxide:

Yes

Foam: Yes

Dry Chemical:

Yes

Halon: Yes

Other:

Do not use water jet.

5.2 UNUSUAL FIRE AND EXPLOSION HAZARDS:

Specific Hazards Arising from the Chemical: Flammable liquid and vapor. Vapors may form explosive mixtures with air. Runoff to sewer may create fire or explosion hazard. Vapors are heavier than air and may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Hazardous combustion products may include carbon oxides and nitrogen oxides.

Explosion Sensitivity to Mechanical Impact: No

Explosion Sensitivity to Static Discharge: No

5.3 SPECIAL FIRE-FIGHTING PROCEDURES:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Evacuate surrounding areas. Do not touch or walk through spilled material. Shut off all ignition sources. Avoid breathing vapor or mist. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

6.2 ENVIRONMENTAL PRECAUTIONS:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution.

6.3 SPILL AND LEAK RESPONSE:

Small spills: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert dry material and place in an appropriate waste disposal container.

Large spills: Stop leak if without risk. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in container for disposal (see Section 13). Dispose of via a licensed waste disposal contractor.

SECTION 7. HANDLING and STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING:

Put on appropriate personal protective equipment. Avoid contact with skin, eyes and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Keep container tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical equipment and only non-sparking tools. Take precautionary measures against electrostatic discharges. Smoking, eating and drinking should be prohibited in the application area. Contaminated work clothing should not be allowed out of the workplace. Wash hands thoroughly after handling.

7.2 STORAGE AND HANDLING PRACTICES:

Storage Conditions: Store in a dry, cool and well-ventilated area, protected from direct sunlight and away from incompatible materials, food and drink. Keep container tightly closed. Eliminate all ignition sources. Incompatible

Materials: Strong oxidizing agents, strong acids and strong bases.

7.3 SPECIFIC USES:

See Section 1.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 EXPOSURE PARAMETERS:

Chemical Name	CAS#	ACGIH TLV	OSHA TWA
Bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	136210-32-7	Not Established	Not Established
Polyester Polyurea Resin	136210-30-5	Not Established	Not Established
Proprietary Ingredient 1	Proprietary	Not Established	Not Established
Propylene Glycol Methyl Ether Acetate	108-65-6	Not Established	Not Established
Proprietary Ingredient 2	Proprietary	Not Established	Not Established
Solvent naphtha (petroleum), light aromatic	64742-95-6	Not Established	Not Established
2,6-Dimethylheptan-4-one	108-83-8	TWA 25 ppm	TWA 50 ppm (290 mg/m3)

8.2 EXPOSURE CONTROLS:

VENTILATION AND ENGINEERING CONTROLS: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Use explosion-proof ventilation equipment.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program.

EYE PROTECTION: Safety eyewear complying with an approved standard should be worn; chemical splash goggles if a risk assessment indicates a higher degree of protection is necessary.

HAND PROTECTION: Chemical-resistant, impervious gloves (e.g., nitrile rubber or neoprene) complying with an approved standard should be worn at all times when handling this product if a risk assessment indicates this is necessary.

BODY PROTECTION: Personal protective equipment for the body should be selected based on the task being performed and the risks involved. When there is a risk of ignition from static electricity, wear antistatic protective clothing.

SECTION 9. PHYSICAL and CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE (Physical State) and COLOR: Liquid; Clear, slightly amber

ODOR: Mild solvent odor

ODOR THRESHOLD: Not Available

pH: Not Available

MELTING/FREEZING POINT: Not Available

BOILING POINT: Not Available

FLASH POINT: Not Available

EVAPORATION RATE (n-BuAc=1): Not Available

FLAMMABILITY (SOLID, GAS): Not Available

UPPER/LOWER FLAMMABILITY OR EXPLOSION LIMITS: Not Available

VAPOR PRESSURE (mm Hg @ 20°C (68°F): Not Available

VAPOR DENSITY: Not Available

RELATIVE DENSITY: 1.05

SPECIFIC GRAVITY: 1.05

SOLUBILITY IN WATER: Insoluble

WEIGHT PER GALLON: 8.79 lbs/gallon

PARTITION COEFFICIENT (n-octanol/water): Not Available

AUTO-IGNITION TEMPERATURE: Not Available

DECOMPOSITION TEMPERATURE: Not Available

VISCOSITY: 500 cP (centipoise)

9.2.1 INFORMATION WITH REGARD TO PHYSICAL HAZARD CLASSES

EXPLOSIVES: Not Available

FLAMMABLE GASES: Not Available

AEROSOLS: Not Available
OXIDISING GASES: Not Available
GASES UNDER PRESSURE: Not Available
FLAMMABLE LIQUIDS: Category 3 (see Section 2)
FLAMMABLE SOLIDS: Not Available
SELF-REACTIVE SUBSTANCES AND MIXTURES: Not Available
PYROPHORIC LIQUIDS: Not Available
PYROPHORIC SOLIDS: Not Available
SELF-HEATING SUBSTANCES AND MIXTURES: Not Available
SUBSTANCES AND MIXTURES, WHICH EMIT FLAMMABLE GASES IN CONTACT WITH WATER: Not Available
OXIDISING LIQUID: Not Available
OXIDISING SOLID: Not Available
ORGANIC PEROXIDES: Not Available
CORROSIVE TO METALS: Not Available
DESENSITISED EXPLOSIVES: Not Available
GASES UNDER PRESSURE: Not Available

9.2.2 OTHER SAFETY CHARACTERISTICS

MECHANICAL SENSITIVITY: Not Available
SELF-ACCELERATING POLYMERISATION TEMPERATURE: Not Available
FORMATION OF EXPLOSIBLE DUST/AIR MIXTURES: Not Available
ACID/ALKALINE RESERVE: Not Available
EVAPORATION RATE: Not Available
MISCIBILITY: Not Available
CONDUCTIVITY: Not Available
CORROSIVENESS: Not Available
GAS GROUP: Not Available
REDOX POTENTIAL: Not Available
RADICAL FORMATION POTENTIAL: Not Available
PHOTOCATALYTIC PROPERTIES: Not Available

SECTION 10. STABILITY and REACTIVITY

10.1 REACTIVITY:

No specific test data related to reactivity available for this product or its ingredients.

10.2 STABILITY:

The product is stable.

10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 CONDITIONS TO AVOID:

Avoid heat, sparks, open flames and static discharge. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

10.5 MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:

Reactive or incompatible with strong oxidizing agents, strong acids and strong bases.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS:

Under normal conditions of storage and use, hazardous decomposition products should not be produced. If decomposition occurs (e.g., in a fire), products may include carbon dioxide, carbon monoxide, nitrogen oxides.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

TOXICITY DATA:

Chemical Name	CAS#	Oral LD50	Dermal LD50	Inhalation LC50
Bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	136210-32-7	>2000 mg/kg (Rat)	>2000 mg/kg (Rat)	>4224 mg/m3 (Rat) 4h
Polyester Polyurea Resin	136210-30-5	>2000 mg/kg (Rat)	>2000 mg/kg (Rat)	>4224 mg/m3 (Rat) 4h
Proprietary Ingredient 1	Proprietary	>2000 mg/kg (Rat)	>2000 mg/kg (Rat)	>4224 mg/m3 (Rat) 4h
Propylene Glycol Methyl Ether Acetate	108-65-6	No Data Available	No Data Available	No Data Available

Chemical Name	CAS#	Oral LD50	Dermal LD50	Inhalation LC50
Proprietary Ingredient 2	Proprietary	>5000 mg/kg (Rat)	No Data Available	No Data Available
Solvent naphtha (petroleum), light aromatic	64742-95-6	>4000 mg/kg (Rat)	>3480 mg/kg (Rabbit)	3670 ppm (Rat) 4h
2,6-Dimethylheptan-4-one	108-83-8	>2000 mg/kg (Rat)	>2000 mg/kg (Rat)	>14 mg/L (Rat)

CARCINOGEN CLASSIFICATION: None of the ingredients present at or above 0.1% is listed as a carcinogen by IARC, NTP, ACGIH or OSHA.

Acute toxicity	Based on available data, the classification criteria are not met
Skin corrosion / irritation	Based on available data, the classification criteria are not met
Serious eye damage / irritation	Based on available data, the classification criteria are not met
Respiratory or skin sensitization	Skin Sensitization Category 1 (May cause an allergic skin reaction)
Germ cell mutagenicity	Based on available data, the classification criteria are not met
Carcinogenicity	Based on available data, the classification criteria are not met
Reproductive toxicity	Based on available data, the classification criteria are not met
STOT-single exposure	Based on available data, the classification criteria are not met
STOT-repeated exposure	Based on available data, the classification criteria are not met
Aspiration hazard	Based on available data, the classification criteria are not met

SYMPTOMS OF OVEREXPOSURE BY ROUTE OF EXPOSURE: Skin Contact: May cause an allergic skin reaction (redness, itching, rash). Eye Contact: High vapor concentrations may cause slight irritation. Inhalation and Ingestion: No known significant effects or critical hazards.

ACUTE:

INHALATION: No known significant effects or critical hazards; high vapor concentrations may irritate the respiratory tract.

CONTACT WITH SKIN: May cause an allergic skin reaction.

EYE CONTACT: May cause slight irritation.

INGESTION: No known significant effects or critical hazards.

CHRONIC: Repeated or prolonged skin contact may cause sensitization (allergic contact dermatitis).

TARGET ORGANS: Acute: Skin Chronic: Skin (sensitization)

SUSPECTED CANCER AGENT: Not classified. None of the ingredients present at or above 0.1% is listed as a carcinogen by IARC, NTP, ACGIH or OSHA.

IRRITANCY OF PRODUCT: This product may cause slight skin and eye irritation.

SENSITIZATION TO THE PRODUCT: May cause an allergic skin reaction (Skin Sensitization Category 1). The aspartic ester components were sensitizers in guinea pig maximization testing.

REPRODUCTIVE TOXICITY INFORMATION: No data available for this product; classification criteria are not met.

SPECIFIC TARGET ORGAN TOXICITY-SINGLE EXPOSURE: Not classified.

SPECIFIC TARGET ORGAN TOXICITY- REPEATED EXPOSURE: Not classified.

ASPIRATION HAZARD: Not classified (light aromatic solvent naphtha present at less than 1.5%).

11.2 INFORMATION ON OTHER HAZARD CLASSES WHICH RELATES TO ENDOCRINE DISRUPTING PROPERTIES:

No specific data available for this product.

SECTION 12. ECOLOGICAL INFORMATION

12.1 TOXICITY:

See component ecotoxicity table below.

Chemical Name	CAS #	Aquatic Toxicity
Bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	136210-32-7	Acute LC50 66 mg/L (96h, Danio rerio); Acute EC50 88.6 mg/L (48h, Daphnia magna); Acute IC50 113 mg/L (72h, Scenedesmus subspicatus)
Polyester Polyurea Resin	136210-30-5	Acute LC50 66 mg/L (96h, Danio rerio); Acute EC50 88.6 mg/L (48h, Daphnia magna); Acute IC50 113 mg/L (72h, Scenedesmus subspicatus)
Proprietary Ingredient 1	Proprietary	Acute LC50 66 mg/L (96h, Danio rerio)
Proprietary Ingredient 2	Proprietary	Acute LC50 >9.9 mg/L (96h, zebra fish)

12.2 PERSISTENCE AND DEGRADABILITY:

The aspartic ester components (CAS 136210-32-7, 136210-30-5) are not readily biodegradable (13% in 28 days, comparable product). No further data available for other components.

12.3 BIOACCUMULATIVE POTENTIAL:

See component bioaccumulation table below.

Chemical Name	CAS #	Bioaccumulative Potential
Bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	136210-32-7	BCF 8.2 (calculated; low potential)

12.4 MOBILITY IN SOIL:

No specific data available on this product.

12.5 RESULTS OF PBT AND vPvB ASSESSMENT:

No specific data available on this product.

12.6 OTHER ADVERSE EFFECTS:

Harmful to aquatic life with long lasting effects.

12.7 WATER ENDANGERMENT CLASS:

May be water endangering in accordance with EU Guideline 91/155-EWG. Do not allow product to reach ground water, water course or sewage system.

SECTION 13. DISPOSAL CONSIDERATIONS
13.1 WASTE TREATMENT METHODS:

The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues; do not cut, weld or grind used containers unless cleaned thoroughly internally.

13.2 EU WASTE CODE:

Not determined.

SECTION 14. TRANSPORTATION INFORMATION

US DOT, IATA, IMO, ADR:

U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS: This product is classified (per 49 CFR 172.101) by the U.S. Department of Transportation, as follows.

14.1 UN IDENTIFICATION NUMBER:	UN1263
14.2 PROPER SHIPPING NAME:	PAINT
14.3 HAZARD CLASS NUMBER and DESCRIPTION:	Class 3 (Flammable Liquid)
14.4 PACKING GROUP:	III
DOT LABEL(S) REQUIRED:	Flammable Liquid
NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER:	128
14.5 ENVIRONMENTAL HAZARDS: (RQ QUANTITY):	None
MARINE POLLUTANT:	No.
14.6 SPECIAL PRECAUTION FOR USER:	None

INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA): UN1263, PAINT, Class 3, Packing Group III.

INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO): UN1263, PAINT, Class 3, Packing Group III.

SECTION 15. REGULATORY INFORMATION
15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE SUBSTANCE OR MIXTURE:
UNITED STATES REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: This product does not contain any chemicals subject to SARA 313 reporting at or above de minimis levels.

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for the components of this product. The default Federal SDS submission and inventory requirement filing threshold of 10,000 lbs (4,540 kg) therefore applies, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): See current shipping/regulatory documentation for reportable quantities of listed components.

U.S. TSCA INVENTORY STATUS: The components of this product are listed on the TSCA Inventory or are exempted from listing.

OTHER U.S. FEDERAL REGULATIONS: None known

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): This product does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

15.2 CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS: Components are DSL Listed, NDSL Listed and/or are exempt from listing

OTHER CANADIAN REGULATIONS: Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by those regulations.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: This product is a classified per WHMIS 2022 Hazardous Product Regulations.

15.3 EUROPEAN ECONOMIC COMMUNITY INFORMATION:

This product meets the definition of a hazardous substance or preparation as defined by the European Union Council Directives 67/548/EEC, 1999/45/EC, 1272/2008/EC and subsequent Directives.

See Section 2 for Details

CHEMICAL SAFETY ASSESSMENT:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

15.4 AUSTRALIAN INFORMATION FOR PRODUCT: Not determined.

15.5 JAPANESE INFORMATION FOR PRODUCT:

JAPANESE MINISTER OF INTERNATIONAL TRADE AND INDUSTRY (MITI) STATUS: Not determined.

15.6 INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac: Not determined

Australian Inventory of Chemical Substances (AICS): Not determined

Korean Existing Chemicals List (ECL): Not determined

Japanese Existing National Inventory of Chemical Substances (ENCS): Not determined

Philippines Inventory of Chemicals and Chemical Substances (PICCS): Not determined

Swiss Giftliste List of Toxic Substances: Not determined

U.S. TSCA: Listed

SECTION 16. OTHER INFORMATION

ABBREVIATIONS AND ACRONYMS:

EPA: United States Environmental Protection Agency

ARD: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) - Health: 2*, Flammability: 2, Physical Hazards: 0

PREPARED BY: Chris Eigbrett – (MSDS to GHS Compliance)

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of the need that information is current, applicable and suited to the circumstances of use. Bayvex Technologies assumes no responsibility for injury to vendee or third party person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, Bayvex Technologies assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.

REVISION LOG

October 17, 2026

- Document creation

END OF SDS SHEET